

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

1

## Preamble:

Action lengths, magazine capacities, chamber dimensions and freebore can be *different* for every rifle, even within the same cartridge/caliber. This can affect the potential COAL and CBTO for *every rifle*. Measure AND establish both the maximum COAL and CBTO for YOUR rifle before loading any bullet, including Hammers. Do not simply follow generic guidelines. Never *Assume* these loads will work in Your rifle. *Always measure and verify!*

Since the COAL and CBTO measurements are unique to each rifle listed, any changes to those dimensions *can affect pressure*. The loads listed were deemed safe in those specific rifles by the submitter of that load. Use standard safe reloading practices to work up a safe load in your rifle.

Hammer HHT Load Data (rev 1: 6-6,15-23)(7-3, 17)(8/23)(9/11)( 10/3,10/17)(11/15)(12/3, 12/22)(1-5-24)(2/3, 2/27)(3/28)(5/1)

22 NOSGAR (pgaines) (22 Nosler using 6mm Hagar brass)	57 HHT	20", 1-8", AR 15	Hagar, 1/4" crimp	CCI 450	????	2000 MR	32.0 - 36.6 36.3	3151  3534 3508	Start  max, no pressure final load, es6, sd3, 0.33" group
22 CM (Killer traylor)	62 HHT	22", Tw ???	Lapua srp	F 205	.020 jump	H 100V	43.0	3400	No pressure
223 Rem (The Tinkerer)	68 HHT (**Bolt gun data)**	20", Howa mini Tw ???	Lake City, 1X, no crimp	CCI 450	2.360 OAL	A2460  A2230	24.5 24.8 25.1 25.3 25.5  22.9 23.3 23.6 23.9 24.2 24.4 24.6 24.8	2844 2881 2901 2913 2922  2730 2787 2799 2959??? 2914 2921 2943 2992	Start at 23.5       start at 22.5, mild pressure, start with crimp. Unless you need this for a gas gun, use Terminator instead. Charges same

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------------	----------------------------	----------------------	--------	------	--------	--------	----------	---

2

[illegible]

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

3

22 CM (Killer traylor)	68 HHT	22", Tw ????	Lapua srp	F 205	.020 jump	N 555	45.0 45.5	3530 ?	No pressure, heavily compressed
22 CM (slickyboyboo)	68 HHT	20", 1-7.7" Bartlein	Alpha	CCI 450	2.580 OAL	RI 16	41.5 41.7 41.9 42.1 42.3 42.5 42.7 42.9 43.1	3473 3485 3493 3548* 3540* 3556* 3608 3626 3654	*potential node  very faint ejt faint ejector ejector, bolt lift
	68 HHT	Same	Alpha	CCI 450		SW Precision	37.4 37.6 37.8 38.0 38.2 38.4 38.06 38.8 39.0	3425 3470 3475 3495 3506 3516 3546 3546 3561	light ejt marks potential node, same, lt ejt marks ligt ejt marks
22 CM (Mojo)	68 HHT	24", 1-7.5"	Peterson No crimp	F 210	?????	RL 16	37.0 38.0 39.0 40.0 41.0 42.0 42.5 43.0 43.5 44.0	3188 3217 3311 3412 3526 3600 3624 3638 3700 3732	Faint ejt mark ejt/ext mark

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------------	----------------------------	----------------------	--------	------	--------	--------	----------	---

4

							44.5	3810	ejt/ext/crater primer overpressure																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
22 CM (Mojo)	74 HHT	24", 1-7.5"	Peterson No crimp	F 210	?????	RL 26	39.0	3045																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							40.0	3108																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							41.0	3200																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							42.0	3255																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							43.0	3344																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							44.0	3458																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							44.5	3485																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							45.0	3533																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							45.5	3571																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							46.0	3609	Faint ejt mark																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
							46.5	3623																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
6 Dasher (dustbag)	75 HHT	24", 1-7.5" Proof	Alpha	CCI 450	2.183 (.020 off)	Varget	32.0	3090	Compressed “ “ no pressure signs																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
							32.5	3115																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							33.0	3186																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							33.5	3229																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							34.0	3285																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							34.5	3336																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							35.0	3349																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							35.5	3411																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
																	compressed “ no pressure signs																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
						CFE 223	37.0	3466																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							37.2	3458																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							37.4	3515																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							37.6	3495																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							37.8	3529																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
							38.0	3560																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
													38.2	3562																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

5

						H 335	34.5 35.0	3531 3579	compressed “, heavy bolt
							34.5 35.0 35.5 36.0 36.5	3472 3556 3603 3638 3684	hvy bolt good accuracy with <a href="#">36.2 @ 3681</a> av
243 Win (Afisher)	75 HHT	22", Tw ??? Win Mod 70	Starline, Lt crimp?	Rem 9.5	2.640 OAL	Varget	40.0 40.5 41.0 41.5 42.0	3160 3155 3199 3206 error	A little cratered same ejt swipe???
						Big Game	44.0 44.5 45.0 45.5 46.0	3310 3332 3253? ? 3408	accuracy better with Varget  bad primer
243 Win (unclecroc)	75 HHT	20", 1-10", Wby	Starline	CCI 200	2.700 OAL	IMR 4064	39.0 39.5 40.0 40.5 41.0 41.5 42.0	3258 3286 3325 3346 3440 3466 3567	Flat primer, slight crater
243 Win (Mazroth)	75 HHT	22", 1-10", Tikka	Peterson	BR 2	2.700 OAL	Varget	40.0 40.3	3384 3375	No pressure signs Was hoping for

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

6

							40.6 40.9 41.2 41.5 41.8	3410 3427 3472 3546 3445	3500ish
6mm CM (unclecroc)	90 HHT	28", 1-8", 1885 Highwall	Sig	F 210	2.700 OAL	H 4350	42.0	3220	Es 12, 0.5" grp
6mmRem AI (jmyers)	90 HHT	Benchmark ??? lgth, tw 1-7.5"	Made from 8x57 Mauser .004 nk ten, no crimp	BR 2	2.995 OAL	N 160	50.0 51.0 52.0	3540 av	0.30 moa, 100 yds., es 18 case head expansion .0003 cratered primer
250 Sav AI (King 358)	95 HHT	22", 1-7", McGowen	Hornady 250 Sav, ¼ T FCD	CCI 200	2.531 OAL	Ramshot Hunter  StaBall Match  Big Game	46.5 46.8 47.1 47.4 47.7  42.3 42.5 42.7 42.9 43.1 43.3 43.5 44.0  45.0 45.5	3163 3186 3225 3222 3205  3300 3333 3333 3336 3372 3380 3396 3430  3326 3335	RH may be to slow. Going to try Staball Match       very slight ejt  here & on, ejt marks

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

7

							46.0	3337	
257 Roberts Imp (AKSam)	95 HHT	18", 1-10" McGowen	Privi	CCI 200	2.815 OAL	IMR 4955	47.0 48.0 49.0 50.0	2929 3022 3074 3165	Slight bolt lift ejector mark
257 WBY (newmexkid)	95 HHT	26", 1-10"	Wby	CCI LR	3.250 OAL	IMR 4350	69.0	3730av	0.224 grp, light swipe
257 WBY (bodeen)	95 HHT	26", 1-10"	Wby	F 215	2.795 CBTO	RL 23	67.0 67.5 68.0 67.2	3450 3460 3519 ?	Bolt, ejt 0.75@200
257 Wby (fertsales)	95 HHT	26"? factory	Norma 1x	F 215	2.754 CBTO	RL 25	75.2	3663 av	Es9, sd5, .483 @100 yds
257 Wby (pgaines)	95 HHT	26", 1-10",	Wby, ¼ crimp	F 215	3.147 OAL	RL 26	72.3 - 75.5 74.0	3622  3895 3806	start  Hvy bolt es 18, sd8, .67"
25-06Al (jmyers)	127 HHT	???", 1-7.5"	Lapua, no crimp, .004 nk ten	CCI BR2	????, .030 jump	N 570	64.5	3275	.25 moa to 200, drop tube, es 14
6.5 Grendel (Riceman)	80 HHT	22", 1-8" Howa mini	Nosler	CCI BR 4	2.143 OAL	H 322 A 2520	31.0 34.0	3154 av 3054 av	Max fill, compressed max fill, compress
6.5 CM (just jon)	80 HHT	26", 1-7"	Lapua new, 1/8T crimp	F 210	2.517 OAL	BL-C(2)	44.3 44.8 45.3	3567 3587 3630	

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

8

							45.8 46.3	3672 3701	No pressure signs
6.5 CM (Richcotte)	80 HHT	18", 1-8", Ruger M77	LC11 brass converted	WLR	2.648 OAL	H 4350  Varget	38.0 39.0  38.0 39.0 40.0 41.0 42.0 43.0 44.0 45.0	2540 2592  2934 3057 3132 n/r 3235 n/r 3387 3453	No pressure yet?
6.5 CM (RLL)	80 HHT	20", 1-8", suppressed	Lapua	CCI 450	2.518 OAL	Varget	41.0 42.0 43.0 44.0 45.0 46.0 47.0	3060 3163 3262 3376 3408 3511 3604	Start compressed case head shine light bolt, shine bolt, primer flatten, bolt face shine(ejt?)
260 Rem (just jon)	80 HHT	20", 1-9"	Nosler new, 1/8T crimp	F 210	2.652 OAL	BL-C(2)       H 4895	41.0 42.0 43.0 44.0 45.0 46.0 47.0 48.0  37.8	3098 3195 3226 3222 3288 3392 3485 3553  3035	No pressure signs



# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

9

							38.8 39.8 40.8 41.8 42.8 43.8 44.8	3080 3115 3221 3300 3340 3440 3562	Lt ejt swipe Hvyejt + bolt, stop
6.5 PRC (DiscoSteve)	80 HHT	20", 1-7"	Hornady, 1x, 1/2T FCD	CCI 200	2.672 OAL	Varget	55.0 56.0 57.0 58.0	3562 3656 3732 3766	<b>SF 3.52 ASL</b> <b>4.23@5k ASL!</b> Slt ejt, easy bolt more room left
6.5 Grendel (Outdoor Edventure)	118 HHT	20", 1-8", AR 15	Hornady 3X ¼ T FCD	CCI 450	1.207 CBTO	Lever Evolution      Ramshot X-Term	25.0 26.0 27.0 28.0 29.0  22.0 23.0 24.0 25.0 26.0	2257   2351 2447 2545 2645  2216 2316 2420 2527 2645	Slight pwdr crush 12" drop tube no pressure         no pressure
6.5 CM (Outdoor Edventure)	118 HHT	24", 1-8", Krieger	Hornady 2X	WLRM	2.755 OAL (.005 jump)	H 4350    IMR 4064	44.0 45.0 46.0  38.0 39.0	3031 3106 3165  2897 2947	Early pressure

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

10

							40.0 41.0 42.0	3046 3129 3158	slight shine flat primer blown primer
6.5 CM (litlebighorn)	118 HHT	24", 1-8", Lilja	Lapua new, no crimp	F 210	2.78 OAL	RL 23	43.0 43.5	2858 2883	Mild load mild load, both 0.5
6.5 CM (ittlebighorn)	118 HHT	24", 1-8" Lilja	Lapua new	F 210	2.78 OAL	RL 16	43.5	3056	
6.5 CM (les)	118 HHT	24", 1-8", Tikka T3	Lapua, 1x, ¼ T FCD	CCI BR2	2.780 OAL	StaBall 6.5	45.5	3024	Accuracy node, 3/8"@ 100, pressure @46.2
260 Rem (Jemurr3)	118 HHT	24", 1-8", Sav 110	RP 1X  ¼ T FCD	WLR	2.80 OAL	N 165  N 555  Superformance  H4831SC	42.5 43.5 44.5 45.5 42.0 43.0 44.0 45.0 46.0 43.0 44.0 45.0 46.0 47.0 43.5 44.5	2688 2861 2943 3003 2873 2911 2949 3016 3016 2855 2842 2873 3016 2989 2760 2842	No signs of pressure, either load. Both loads were compressed. Will try N 550 if I can find some.

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

11

							45.5 46.5 47.5	2812 2861 2930	
						Ramshot Hunter	41.5 42.5 43.5 44.5 45.5	2737 2783 2801 2855 2917	42.5-43.5 one ragged hole
						Ramshot Big Game	40.5 41.5 42.5 43.5 44.5	2855 2904 3065 3044 3086	seem to be a node from 42.5-43.5
6.5x284 (littlebighorn)	118 HHT	24", 1-8", Lilja	Lapua new, no crimp	F 210	2.960	RL 23	52.0 52.5	3209 3230	Mild loads, 0.5 moa
						RL16	53.0 53.5 54.0 54.7	3354 3394 3430 3479	ejt swipe, 0.3 moa ejt, tight bolt, stop
6.5-284 (Mlaid)	118 HHT	21", 1-7.5",	Norma1/4 T FCD	CCI 200	3.143 OAL	RL 16	52.0 52.5 53.0 53.5 54.0	3071 3078 3122 3141 3179	Slt ejector
6.5-06 Al (gltaylor)	118 HHT	27", 1-8" Brux	Peterson 280Al formed to 6.5-06Al,	Rem LR	3.271	RL 16	51.0 52.0 53.0 54.0	3159 3205 3264 3301	

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

12

			1/8T FCD				55.0 56.0 57.0	3361 nr 3456	Ejector
				CCI 250		H 100V	55.0 56.0 57.0	nr 3418 3451	light bolt, ejector
						Superformance	59.0 59.5 60.0 60.5 61.0	3441 3466 3494 3527 3540	light cratering cratering, lt clicker primer cratering cratering
						retest	61.0	3553 av	<b>SF = 2.016</b> es29, sd13, elongated ragged hole group
6.5 MAX (gltaylor) (6.5 SAUM IMP)	118 HHT	26", 1-7.5" Brux	ADG X5 1/8 T FCD	Rem LR	2.900 OAL	RL 26	68.0 69.0 70.0	3459 3448? 3546	Light bolt
						RL 23	67.0 68.0* 69.0	3502 3540 3593	compressed, lt bolt hvy bolt, ejt, stop
					a little disappointe d in speeds, but will work for groups next	N 560	67.0 68.0 69.0 70.0* 71.0	3418 3461 3534 3573 3612	lt bolt, compressed lt bolt, ejt/primer ok
						N 550	60.0 62.0 64.0	3443 3524 3650	bolt, lt ejt blew primer, hvy

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

13

			1/8 T FCD		Re-Test/ Refine	H 100V	61.0 62.0 63.0 64.0	3413 3463 3528 3594	bolt, stop  hvy bolt, ejt, stop
			1/4-3/8 T FCD best		0.147 jump	N 560  drop tube from here on+vibrate	69.0 70.0 70.5 71.0 71.5* 72.0 72.5	3456 3503 3563 3598 3598 3639 3684	<b>SF = 2.304 @3600</b>  sd 7, es 13  lt ejt, lite bolt, stop
							71.5	3626av	.284" @ 100yds
6.5 Grendel (Outdoor Edventure)	125 HHT	20", 1-8", AR 15	Hornady 3X ¼ T FCD	CCI 450	1.207 CBTO	Win 748	25.0 26.0 27.0 28.0 28.5	2293 2338 2411 2510 2560	Slight crush crush, no pressure
						IMR 3031 (too fast for Gren del?)	24.0 25.0 26.0	2281 2386 2459	compressed recoil sharp. Stopped
6.5 CM (Outdoor Edventure)	125 HHT	24", 1-8", Krieger	Hornady 2X	WLRM	2.820 OAL .020 jump	Ramshot Hunter	46.0 47.0 48.0 49.0 49.5	n/r 3046 3101 3096 3132	Slt ejt compresd, primer flat primer

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

14

						CFE 223	42.0 43.0	3047 3091	ejt, should've stop blown primer
6.5 CM (rif)	125 HHT	24", 1-7.75", Tikka T3x	Lapua 3x, 3/8 T FCD	F 215	2.726 OAL	Varget	38.5 to 41.0	2795 2996	<b>SF 1.82</b> sd 6.5, es 17 .314 moa@200
6.5 CM (DiscoSteve)	125 HHT	22", 1-8", 1/4T FCD, X-Bolt Pro	Starline new, 1/4T FCD	CCI 200	2.714	IMR 4166	37.0 38.0 39.0 40.0 40.5 41.0	2776 2846 2945 2971 2994 3076	Easy bolt, slt ejt hard bolt, Ejt, stop
						StaBall 6.5	45.0 46.0 47.0	2880 2955 3035	sticky bolt, ejt
6.5 CM (Markus)	125 HHT	22", 1-8", Mod 70	Lapua	CCI BR 2	2.824 OAL	Varget	38.5 40.0* 41.0	2808 2940* 3023	*Accuracy load, 0.3 moa, es 6
6.5 CM (Richcotte)	125 HHT	24", Sav Mod 10	LC 11 (reformed) ¼ T FCD	WLR	2.826 OAL	H 4350	35.0 37.0 39.0 40.0 41.0 42.0 43.0 44.0  42.6	2521 n/r n/r 2777 2841 2931 3003 3047  2937	Hvy bolt, ejt, cratered primer single hole, es33,sd12.2

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

15

6.5 CM (longbow51)	125 HHT	26", 1-8",	Lapua SRP	CCI 400, 59° F	2.820 OAL	Varget	39.0	2900	½ moa @ 400
6.5-284 (MLaird)	125 HHT	21", 1-7.5"	Norma, ¼ T FCD	CCI 200	3.134 OAL	RL 16	51.5 52.0 52.5 53.0 53.5	2937 3997 error 3.64 3095	
6.5 PRC (Mountainman)	125 HHT	26", 1-7.5", Bergara	Lapua (new), ¼ FCD	F 210	2.955 OAL	Superformance	58.5	3330	Sub ½", es 15
6.5 PRC (cubdriver84d)	125 HHT	20", 1-8", Tikka	ADG, 3/8T FCD	F 215	2.860 OAL	H 4831SC	56.0 56.5 57.0 57.5 58.0	2962 2987 2982 3026 3059	Compressed same bolt & ejt
6.5 PRC (DiscoSteve)	125 HHT	20", 1-7"	ADG virgin, no crimp	CCI 200	2.850 OAL	N 565	57.0 58.0 59.0	2829 2844 2898	No pressure, out of room
						StaBall 6.5	55.0 56.0 57.0 57.5 58.0 58.5 56.5	3061 3107 3165 3173 3183 3249 *3065av	no pressure, lots of case cap yet, 1.5 moa  1"@200 1 moa
						4831 SC	55.0 56.0	2848 2906	

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

16

						N 560	57.0	2927	
							57.0	2963	
							58.0	err	
							59.0	3085	
							60.0	3139	no press. 5"
							61.0	3203	<a href="#">vertical@200</a>
							61.0	*3223av	1 moa
						H 4350	50.0	2819	
							51.0	2852	no press, more
							52.0	2916	room, 3"
									<a href="#">horiz@200`</a>
							53.0	2952	
							54.0	2987	no press, more room
6.5 PRC (pgaines)	125 HHT	24", 1-8", CA Ridge	Hornady	CCI 250	2.940 OAL	RL 26	58.3	3285	Start
							60.7	3410	Stop
							59.3	3302	chosen, 0.266 grp!
6.5 PRC (BryanF)	125 HHT	24", 1-7.5", McGowen	Peterson	F 215	2.955 OAL	RL 26	54.0	3150	Sd 15.2, 0.500 moa
6.5 PRC (OG-Danimal)	125 HHT	24", 1-7.5", Proof	ADG, factory crimp die	CCI 250	2.923 mag length, 2.507 OTB	N 560	57.0	3038	Entire series went into a .75 hole!!!
							58.0	3065	
							59.0	3149	
							59.5	3197	
							60.0	3247	
							60.5	3261	nice node 60.5-
							61.0	3262	61.0
							61.5	3285	



# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

17

							62.0	3312	no pressure
6.5 SAUM (Jeremiah Lovelace)	125 HHT	22", 1-8"?, Proof	????	F 210	????	N 560	63.0	3364	Es 11, sd 4.8, .425", slightly sticky bolt
26 Sherman Mag (gltaylor) (300 PRC Imp nk down to 264)	125 HHT	30", 1-7.5", Brux	ADG, 2/8T FCD	CCI 250	3.548 OAL .020 jump	RL 26	68.0 69.0 70.0 70.0	3237 error 3367 3300	Lt ejector av 3 shots, sd5, es14
				Rem 9 ½ LR	Same	Same	72.0	3400av	sd8, es21 all groups ~0.5"
				CCI 250	Same	Hodgdon US 869 (too slow)	86.0 87.0 88.0 89.0 90.0err	3284 3310 3346 3372 ~3398est	SF = 2.0 @3400  whole group one big hole! Very faint ejt
				CCI 250	3.554 OAL	RL 19	74.0 75.0 76.0 77.0 78.0 79.0 80.0	3592 3604 3648 3692 3741 3810 3819	All primers cratered going down  clicker gas leak, ejt, bolt
						need to tune	78.0 77.0	3756 av 3705 av	Too hot, es31, sd12 group ok, 0.6
				Rem 9 ½ 2/8 FCD	same	RL 19	76.0 77.0 78.0	3717 3732 3772	slight bolt

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------------	----------------------------	----------------------	--------	------	--------	--------	----------	---

18

[illegible]

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

19

270 WSM (choperzrul)	122 HHT	23", 1-10", Brown X-Bolt	Norma, 1X, 3/8T FCD	F 215	2.810 OAL	RL 16	60.0 59.7 60.3 60.9 61.5 62.1 62.7	3317 3281 3308 3341 3373 av 3398 err	Seated bullet too long. Need to re-do 0.63"  0.4" ejt, head grew .001
									6.8 Western
270 Win (Thors Hammer) (Muddyboots)	160 HHT	27", 1-8", Rem 700	Petersen 2X, 1/8 T FCD	F 210	3.655 OAL .290 freebore	RL 26	58.0 59.0 60.0 61.0	3079 3100 3167 3212	Ejector ejt., primer crater
6.8 Western (g_rupp)	160 HHT	26", 1-7.5", Brown X-bolt	Win	WLRM	2.942	H 4831sc	60.0	2990	
6.8 Western (hand skills)	160 HHT	24", 1-7.5"	Win, 1/3 T FCD	CCI 200	2.894 OAL	RL 26	57.0 to 64.0 63.0	? ? 3081	Load chosen
280 AI (DaveM)	118 HHT	22", 1-9" Christensen	Petersen 1/4T FCD  1/8T FCD	WLRM	3.264 OAL	StaBall 6.5	61.0 62.0 63.0 63.5 64.0  64.3 64.6 65.0	3370 3441 3462 3507 3538  3542 3596 3622	Stiff bolt. Too hot

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------------	----------------------------	----------------------	--------	------	--------	--------	----------	---

20

			1/8T FCD			H 4350	59.0 60.0 61.0 62.0	3382 3416 3462 3633av(3)	
			1/4T FCD			same	62.0	3603av	
			1/8T FCD	F 210		N 170	59.0 60.0	2899 2953	
				F 210		Magpro	59.0	2934	
		current	load(3/8T)	F 210		Staball 6.5	64.0	3550	feel there's better accuracy to get
7mm Sherman MAX (JTH)	118 HHT	24", 1-8", Proof	ADG Sherman, crimped, 0.0025 nk tn	F 210	2.785 OAL	H 4350	65.0 66.0 67.0 68.0 69.0  67.5	3419 3489 3538 3588 3634  3560av	Faint ejector <b>SF 2.60</b> es 20, 1 hole@200!
7mm Rem Mag (RLL)	118 HHT	26", 1-9.5",	Norma	F 215	3.254 OAL	N 560	63.0 65.0 66.0 67.5 68.0 68.5	2890 2990 3072 3149 3144 3169	No pressure noted. More room to go. A little disappointed in speed. May go to a faster powder.
28 Nosler (Shinbone)	118 HHT	26", 1-8.5", Fierce Edge	ADG, annealed & fired, no crimp	F 215	2.834 OTB	N 565	86.0 89.0 90.0 91.0 92.0	3589 3741 3761 3831 3832	Tight group

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

21

							93.0 93.5 94.0 94.5 95.0 95.5	3890 3914 3935 3957 3978 4000est	est, start drop tube estimated velocity est vel, no pressure est velocity max load, ejt mark
						H 4831  some charges skipped for space	83.5 84.0 85.0 86.0 87.0 88.0 89.0 89.5 90.0	3602 3641 3685 3731 3778 3819 3811 3849 3880	@68F, 0.616"     @68F  ejt mart (light)
7mm/08AI (AKSam)	132 HHT	20", 1-9"	Lapua	CCI 200	2.855 OAL, .050 jump	StaBall 6.5   Varget	48.0 49.0 50.0 51.0c  42.0 43.0 44.0 45.0	2880 2938 3002 3035  2884 2913 2975 3038	Mild bolt lift
284 Win (Mountainman)	132 HHT	20", 1-9"	Petersen, ¼ crimp	F 210	3.032 OAL	N 540	50.5	3000	Es 9, one ragged hole. <b>SF 2.055</b>
280 AI (andron)	132 HHT	24", 1-9"	Peterson new	CCI 200	????	H 4350	52.5 53.0 53.5 54.0	3100 3104 3166 3138	

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------------	----------------------------	----------------------	--------	------	--------	--------	----------	---

22

						N 165	54.5 55.0  61.0 61.5 62.0 62.5 63.0 63.5 64.0 64.5	3197 3129  3073 3198 3220 3263 3316 3330 3334 3373	Velocity all over the place, no pressure      compressed here on  max fill
						StaBall 6.5	56.5 57.0 57.5 58.0 58.2 58.5	3222 3233 3297 3265 3301 3317	slight primer flatten
280 AI (andron)	132 HHT	24", 1-9", Kimber	Peterson, 3/16T FCD	Fiocchi LR	3.330 OAL	N 550 80°F	57.0 57.5 58.0  56.6 56.8 57.0 57.2	3396 3422 3456  3355av 3366av 3390av 3395av	Light ejt ejector  sd 38, es 77 9 & 18 10 & 19 6 & 11, lite bolt
280 AI (AKSam)	132 HHT	22", 1-8"	Peterson	CCI 250	3.330 OAL	RL 16	56.0 57.0 58.0 59.0	3157 3251 3288 3378	Bolt lift, ejector
280 AI (fuzzymarin dave)	132 HHT	26", 1-9", Wby Mk V	Peterson	CCI 200	3.375 OAL	H 4831SC	60.2 - 61.1	3130  3244	<b>SF 1.62</b>

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

23

7 Rem Mag (bodeen)	132 HHT	24", 1-8.5",	FC	F 215	2.744 CBTO, 0.020 jump	RL 23	67.0 67.5 68.0 68.5 69.0 68.0	3349 3337 3370 3376 3404	0.7"@116 yds
7 Rem Mag (Grizz19)	132 HHT	Wby Van, 1-9.5"	Peterson	F 215	0.050 jump	H 4350	67.0	3402	Sun 0.5 moa
7mm WSM (firecracker)	132 HHT	Kimber 8400 Montana, 24", Tw 1-9.5"	Win nickel or Federal	????	2.294 BTO	Ramshot Magnum	76.5 77.0 77.5 77.8 78.1	3335 3378 3426 3443 3489	Sd 3, 0.700 grp
7mm RUMLN (338 RUM neckd down to 7mm)(Rich Coyle)	132 HHT	26", 1-8"	Rem	WLRM	3.767	H 4831	87.0 - 89.5	3600 - 3704	Loaded in ½ gr increments. Whole group was 5/8"!
280 AI (Texas361)	145 HHT	26" 1-8", CarbonSix	Nosler, crimped	CCI 250	3.330 OAL	Staball 6.5	57.0	3216	No pressure sub moa
7 SAUM (ftc)	145 HHT	24", 1-8.4", Proof	ADG 1x, 1/8T crimp	WLR	2.955 OAL	N 560	60.0 61.0 62.0 63.0 64.0 64.4 65.0	3004 av 3062 av 3106 av 3183 av 3221 av 3255 av 3287 av	No pressure found with either powder

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

24

						H 4350	55.0 56.0 57.0 58.0 58.6 59.2	2988 av 3039 av 3085 av 3112 av 3145 av 3166 av	
7 SAUM (clem)	145 HHT	20", 1-8" Proof	ADG, no crimp	CCI 200	2.275 (0.020 jump)	H 4350	57.0 58.0 59.0	3033 av 3065 av 3128 av	1.5" 0.7", sd 7.6 winner hvy bolt, sd 4.2
7mm PRC (BryanF)	145 HHT	22", 1-8", Proof	ADG	F 215	3.340 OAL	RL 26	71.0	3361	Sd 16, .506 moa
7mm Rem Mag (billyjo)	145 HHT	26", Proof, Tw ????	ADG, 3/8t FCD	F 215  CCI	2.812 CBTO  2.797 CBTO	RL 26	68.0 69.0 70.0 71.0 71.5 72.0  70.0	3310 av 3360av 3421av 3461 3490av 3517av	.75moa @300  Slight clickers clicker clicker  0.2 moa@300!
7mm Rem Mag (Bojo34)	145 HHT	24", 1-8",	ADG, 1X, annealed, 1/4T FCD	F 215	2.670 OTB, 0.010 jump	H 4831sc	71.5	3303	<b>2.014 SF</b>
28 Nosler (Mountainman)	145 HHT	26", 1-8", Bartlein	Nosler 1/8T FCD	F 215	3.630 OAL	N 560	85.0	3569	Es 8, <0.75 grp
7 SAUM (clem)	162 HHT	20", 1-8", Proof	ADG, no crimp	CCI 200	2.960 OAL, 0.030 jump	RL 26	60.0 61.0	2913 av 2934 av	0.53" winner 0.8"



# Hammer HHT Load Data Post

25

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
25									
							62.0 63.0	2987 av 3029 av	1.25" ejt swipe, bolt
7 PRC (Bleeb)	162 HHT	22" Proof, 1-8"??, Sav 110 ULight	Hornady 2x	F 215	3.277 OAL, .075 jump	IMR 7828 ssc	62.0 63.0 64.0 65.0 66.0 66.5 67.0 67.5	2842 2881 2954 2995 3049 3060 3095 3127	Ejector swipe blew primer, primer pocket loose
			Hornady 1x, .002 nk ten	same, 34°F	.065 jump, 2.629 OTB	VV N 165	66.2	3029 av	good ES, group <0.75"
7mm PRC (Ndravetsky)	162 HHT	24", Tw ??, HMR Carbon	ADG, .003 nk ten	F 215	3.320 OAL, 3.342 OTB	N 560	62.0 63.0 64.0 65.0 66.0 67.0 68.0  68.0 66.0	2868 2926 2984 3024 3100 3143 3201  3215 av 3100	Slight ejt mark  no ejt mark ~0.75" 0.5", 1"@200, <b>SF 1.48 @SL</b> <b>SF 1.68@ 3700 ft</b>
7mm PRC (BryanF)	170 HHT	24", 1-8", Proof	ADG  Peterson	F 215	3.340 OAL  3.336 OAL	RL 26  RL 26	67.0  67.0	3087  3066	Sd 4.1, .375 moa  .444 moa, SD 3.0

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

26

7mm PRC (pgaines)	170 HHT	22", 1-8", CA Ridgeline	ADG	F 215	3.160 OAL	RL 26	66.3	2998	Start
							68.4	3091	stop
							67.6	3060	hunt load, 0.19grp!
7mm PRC (Korhill78)	170 HHT	24", 1-8"	Petersen	CCI 200	2.626 OAL? 0.040 jump	N 560	65.5	3030	0.5" @ 100 yds
30-06 (DiscoSteve)	138 HHT	21", 1-8",	Nosler new, 1/3T FCD	CCI 200	3.242 OAL	Varget	54.0 55.0 56.0 57.0	2964 3100 3159 3206	Ejt, bolt lift
308 Win (BFD)	154 HHT	22", 1-10" Aero Solus /Bartlein	Lapua, light taper crimp	F 215	2.765    2.800	IMR 3031	40.5	2700	Group 0.15!!!!    Group 0.32!!!
						A 2520	44.0	2770	
						TAC	43.0	2767	
						IMR 3031	41.5	2740	
						TAC	44.0	2806	
308 Win (DiscoSteve)	154 HHT	16", 1-10", Christensen MPR	Nosler, ½ T FCD, 2X Lapua new, ½ T	CCI 200  F 215	2.800 OAL	4166	43.5	~2608	Just under moa
						TAC	42.5 43.0 44.0	2640 2658 av 2800	just over moa same 0.31 grp!
						AA2520	44.0	2770	0.30 grp!
308 Win	154 HHT	Rem 700,	LC 15,	WLR	????	TAC	42.0	2677	

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

27

(Richcotte)		24", 1-12",				@46gr, at my altitude SF is 1.649. good to 700 yds	43.0 44.0 45.0 46.0 47.0	2706 2791 2800 2940 2990**	**Compressed, It bolt, flat primer
308 (cubdriver84d)	154 HHT	16", 1-9", Carbon6	ADG, 3/8 T FCD	F 215	2.800 OAL	8208 XBR  Bench mark	43.0 44.0 44.5  41.0 42.0 42.5 42.5 43.0	2712 2740 2778  err " 2716 2719 2730	All compressed  ejector  compressed  ejector, bolt, stop
30-06 (Discosteve)	154 HHT	Tikka T3, 22", 1-11"	????, 1/2 T	F 215	3.257 OAL	Ramshot Big Game  Staball 6.5	52.0 53.0 54.0 55.0  59.0 60.0 61.0	2736 2811 2830 2886  err err 3064	No pressure, 1.2" grp with all shots      1 moa all shots
30-06 (Santiam)	154 HHT	1947 Win Mod 70, 24", 1-10"	R-P, no crimp. Nk tn .002	F 210	3.273 OAL	IMR 4451	56.0 56.5 57.2 57.6 57.8 58.0 58.2	2918 2946 2968 3005 3011 3016 n/shoot	57.8 is max per Hodgdon. No pressure didn't shoot

## Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------------	----------------------------	----------------------	--------	------	--------	--------	----------	---

28

[illegible]

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

29

300 WSM (Cryptic Comma)	154 HHT	20", Tw ?????	Norma	F 215	2.855 OAL (0.025 jump)	Varget	56.5 57.0 57.5 58.0 58.5 59.0 59.5 60.0	2981 av 3010 " 3024 " 3065 3101 3120 3142 3172	0.75 grp 0.48 grp 0.99  slightly sticky bolt 0.77 grp, same sticky bolt, ejt
300 WSM (joevh)	154 HHT	23", 1-11", Tikka T3	Win, 20 lb. LFCD	F 215	2.87 OAL, 0.050 jump	R 16	67.0 68.0 69.0 70.0 71.0 72.0	3126 3182 3245 3276 3315 av 3364	0.25", es12, sd 5 Hard bolt lift
300 H&H (Mountainman)	154 HHT	26", 1-10" Wby Mark V, Bartlein	Win	F 215	3.613 OAL	N 550	71.5	3484	Sub 0.75, es 14
300 Win Mag (JustJay)	154 HHT	22", 1-8", X-Bolt SR	Lapua, ¼ T FCD	F 215	3.410 OAL	IMR 4350  H 380	74.0 75.0  68.0 69.0 70.0 71.0	3319 3310  3213 3162 3216 3297	(Short throat) Lt ejt, compressed  all inside 0.7moa plenty case capacity left. Will continue
300 Win Mag (Muddyboots)	154 HHT	26", 1-10", Rem 700	R-P, ¼ T FCD	F 215	2.935 OTB, 3.531 OAL 0.321 jump!	Ramshot Hunter (hoped for better. Disappoint ed) maybe	76.0 77.0 78.0 79.0 80.0 81.0	3267 3300 3316 3384 3410 3436	Slight ejector slt ejt mod ejt, stop

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

30

			Petersen Long, 2X, ¼ T FCD	F 215	2.935 BTO 3.531 OAL yep! .321 jump	brass?  H 4350	74.0 75.0 76.0 77.0 78.0 79.0 80.0 81.0	3358 3401 3445 3490 3555 3555? 3613 3663	ejt & bolt
						RL 16	73.0 74.0 75.0 76.0 77.0 78.0	3358 3350? 3392 n/r 3472 3518	no pressure
300 Win Mag (Richcotte)	154 HHT	24.3", 1-10", Tikka T3X	Peterson Long, 1x, ¼ T FCD	WLR	3.373 OAL	H 4350	79.0 80.0 81.0 82.0 83.0  80.8	3503 3597 3626 3650 3691  3634av	Lt ejector Hvy bolt, Ejt, cratered primer 0.38moa 200 yds
30 Nosler (shinbone)	154 HHT	26", 1-9", Factory	Nosler, 1/8 T FCD	F 215	2.789 OTB	H 4831	83.0 84.0 85.0 86.0 87.0	3379 3467 3491 3610 3672	Slt ejt., good group ejt mark
						N 560	85.0 86.0 87.0	3492  ~3617est	

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------------	----------------------------	----------------------	--------	------	--------	--------	----------	---

31

							88.0 89.0	3679 3770	88-89 tight group ejt mark
						N 565	80.0 81.0 82.0 83.0 84.0 85.0 86.0 87.0 88.0 89.0	3231 3301 3308 3318 3377 3437 3456 3516 3546 3574	start drop tube slt ejt mark
						RL 26	84.0 85.0 86.0 87.0 88.0 89.0 90.0	3591 3629 3651 3711 <b>3764</b> 3802 3842	slt ejt mark slt ejt, safe load slt clicker, ejt mark hard bolt lift. Stop
						H 1000	87.0 88.0 89.0	3451 3588 3628	slt ejt slt ejt
						Retumbo	86.0 87.0 88.0 89.0 90.0 91.0 92.0	3427 3486 3537 3563 case full 3648 3656	start drop tube vibrate. No room
						N 568	80.0	2899	

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

32

							81.0 82.0 83.0 84.0 85.0 86.0 87.0 88.0 89.0 90.0	2968   3089   3197  3278 3296	      start drop tube   too slow. 104% full
300 RUM (joe16)	154 HHT	30", 1-11", Pac Nor	Bertram ½ T FCD	F 215	3.595 OAL	RL 26         H 1000	96.0 97.0 98.0 99.0 101.0 100.0  97.0 98.0 99.0 100.0 101.0	3642 3734 3766 3787 3910av 3875  3508 3555 3593 3623 3663	No pressure " " slight ejt, MAX, Hot 3/8" grp!   no pressure
300 SAUM (jeremy.b.	163 HHT	24", 1-9", Prefered, Tikka	R-P 1X, 1/8 T FCD	CCI 200	3.340 OAL	Varget   RL 26  H 4350	56.0 57.0  68.0  61.0	3083 3135  no vel  3088	.711 lt. Ejt hvy ejt  1.7" grp  0.99, 5 shots no pressure
300 Win Mag	163 HHT	22", 1-8",	Lapua, ¼	F 215	3.720 OAL	IMR 4350	75.0	3132	



# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

33

(JustJay)		Brown X-Bolt	T FCD				76.0 <b>77.0</b>	3207 <b>3245</b>	.210 grp! .198 grp! No press
300 PRC (JTH)	163 HHT	26", 1-8" Bartlein	ADG, 0.025 nk ten, crimped	F 215	3.705 OAL .020 jump	H 4350	72.0 72.5 73.0 73.5 74.0 74.5 75.0 75.5	3168 3214 3254 3251 3279 3299 3295 3335	Faint ejt faint ejt ejector, bolt, clicker
					changed to 3.595. 0.130 jump		74.5 75.0  75.5 76.0	3288 3301  3344 3351	these 2 into same hole @ 200! Faint ejt ejector Sweet spot seems to be 74.7 sub moa
		24", 1-8", Bartlein CF	ADG 3x	F 215	Same	H 4831SC	80.0 81.0 82.0 83.0	n/r 3245 3284 3317	faint ejector
						RL 23	80.0 81.0 82.0 83.0	3311 3331 3367 3408	<b>SF 2.38 for all</b> ejt, stiff bolt
				tested seating depths from .040-.090. More tests	3.695 (.030 jump)		81.7  81.0	3360 av  3395 av	es 10.6, moa group faint ejt, poorer group

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

34

				to come	.070 best so far		80.0 81.7	3347 3384	es 27, 1.00"@ 200 <0.5 moa
300 RUM (joe16)	163 HHT	30", 1-11", Pac Nor	Bertram 1/3 T FCD	F 215	3.995 OAL	RL 26  H 1000	94.0 95.0 96.0 97.0 99.0 98.5  96.0 97.0 98.0 99.0 100.0	3508 3584 3603 3683 3766 av to test  3394 3472 3481 3527 3584	No pressure @85°F safe       no pressure
300 WSM (jrebel)	168 HHT	24", 1-10", Sav 110	Hornady	F215	0.035 jump	H 4350	63.0 63.5	3100 3130	Sub 0.5 moa slt hvy bolt
300 WM (Markus)	168 HHT	25.5", 1-11", Blaser R8	Nosler	F 215	3.452 OAL	H 4350	73.0 75.0	3247 3337	All were 0.7 moa still need to tweak this
300WM (Beeman)	168 HHT	26" Brux, 1-10"	Nosler, 1/4T FCD	F 215	3.541 OAL  0.049 jump	H 4350	70.0 76.0  75.0	Too slow 3346  3321	Start slight ejector. Stop  Final load
300 Wby (riceman)	168 HHT	26", 1-10", #2 bbl	Bertram 1x, 1/4T FCD	F 215	3.569 OAL	RL 23	82.3	3425	0.345 "

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

35

300 RUM (Joe16)	168 HHT	30" Pac Nor, 1-11"	Bertram ½ T FCD	F 215	3.595	RL 26	98.5	3715	7/16 grp
300 RUM (cbjr)	168 HHT	26", 1-8", Browning X-Bolt	Norma new, ½ T FCD	CCI 250	3.746	N 165	85.0 87.0 89.0 91.0 92.0 93.0 94.0	3110 3250 3306 3398 3445 3484 3517	Lt ejt, ¾ moa, will tune with crimp
300 WM (cubdriver)	182 HHT	24", 1-10", Proof	ADG, 3/8T FCD	F 215	3.550 OAL	RL 23	70.0 71.0 72.0 72.5	3049 3094 3092 3121	All compressed
300WM (Bojo34)	182 HHT	26", 1-9", Bartlein	Lapua 1X, 1/4T FCD	F 215	2.840 (crimp top groove)	H 4831sc (pressure 1 gr below 181 HH)	76.0 77.0	3180 3240	Sd 12.8, es 25 Pressure <b>SF 1.876</b>
300 PRC (LocalJW)	182 HHT	22", Tw ??, Seekins	Lapua	Win ???	????	RL 26  N 570  H 1000	79.0 80.0 81.0 82.0  83.0 84.0 85.0  79.0 80.0 81.0	3130? ? 3274 3293  3056 3021 3057  3038 3061 3118	Pressure  ?

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

36

						N 568	82.0 82.5 83.0 83.5 84.0 84.5  84.0 86.0 87.0 87.5 88.0 88.5	3124 3116 3145 3164 3153 3172  3012 3063 3139 3121 3127 3182	
300 PRC (pgaines)	182 HHT	Fierce Carbon, length ???, 1-9" Tw	Hornady no crimp yet	F 215	3.600 OAL	H 1000	83.2 - 85.9 83.6	3187  3290 3252	Sticky bolts 6, sd 3, .75"
300 PRC fuzzymarina (dave)	182 HHT	26", 1-8", X-Bolt	ADG, Lee FCD, amount?	CCI 250	3.630 OAL	H 1000	80.8 - 85.4	3120  3280	<b>SF 2.12</b> 0.5 moa@200
30 Nosler (BryanF)	182 HHT	24", 1-10" HS Precision	Petersen	F 215	3.500 OAL	RL 26	80.0	3212	SD 16.0, .390 moa
300 Warlock (mountainman (30 Nosler wildcat)	182 HHT	28", 1-9"	Nosler, 1/4 T FCD	F 215	3.640 OAL	H 4831	81.0	3330	Es 5, one ragged hole! <b>SF 2.039</b>
300 RUM (BryanF)	182 HHT	26", 1-10", HS	Peterson	F 215	3.600	Retumbo	96.0	3334	SD 8.7, .500 moa

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------	----------------------	----------------	--------	------	--------	--------	----------	---

37

		Precision							
30/378 Wby (Mackay)	182 HHT	26", 1-10", Proof	Wby (fired)	CCI 250	3.820	Retumbo	108 109 110 skip for space 116 117 118	2964 3001 3022  3192 3235 3280	
						50 BMG	108 109 110 111 112 113 114 115 116 117 118	2964 3001 3022 3044 3095 3109 3153 3172 3192 3235 3280	
300 PRC (JTH)	203 HHT	26", 1-8", Proof	ADG 3x	F 215	3.685	N 570	79.0 80.0 81.0	3057 3087 3093	<a href="#">1.07@200!</a> Faint ejector ejector <b>SF 2.16</b>
300 PRC (M88homan)	203 HHT	22", 1-8", suppressed	ADG new	CCI 250	3.645 OAL	H 1000	77.0	2900	1 ragged hole @200! <b>SF 1.8</b>
30/378 Wby (Mackay)	203 HHT	26", 1-10", Proof	Wby (fired)	CCI 250	3.820 OAL	50 BMG	108 109 110 skip for	2995 2962 2985	

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------------	----------------------------	----------------------	--------	------	--------	--------	----------	---

38

[illegible]

# Hammer HHT Load Data Post

Cartridge	Hammer HHT Bullet Weight	Barrel Length/ twist	Brass and Prep	Primer	COAL	Powder	Charge	Velocity	Stability Factor @60° / sea level Notes
-----------	--------------------------------	----------------------------	----------------------	--------	------	--------	--------	----------	---

39

[illegible]