

## 7mmPRC Load/ Cartridge Data-Berger Bullets

Bullet	*Max COAL	*Max CBTO	**Freebore w/ ogive touching	G1 BC	G7 BC
150 Classic	3.010	2.469	0.179	0.505	0.258
168 VLD Target	3.186	2.462	0.172	0.628	0.322
168 VLD Hunt	3.188	2.46	0.170	0.618	0.316
168 Classic	3.119	2.556	0.266	0.566	0.290
175 Elite	3.295	2.555	0.265	0.656	0.336
180 Hybrid Target	3.282	2.523	0.233	0.680	0.349
180 VLD Hunt	3.263	2.536	0.246	0.673	0.345
190 LR Hybrid Target	3.394	2.624	0.334	0.751	0.384
195 EOL	3.398	2.636	0.346	0.755	0.387

SAAMI Specs-Breech to Leads including headspace is 2.540

[Public Introduction - 7mm Precision Rifle Cartridge - 2022-06-16 \(saami.org\)](#)

Brass base to neck junction measure used is 2.000"

\*Max- Bullet boat-tail/ bearing surface junction aligns with brass neck/ shoulder junction

\*\*Freebore is from breech to lead including headspace//SAAMI is 0.250

[Bullet Reference Charts | Berger Bullets](#)