


A = .9665"
B = .9670"
C = .8170"

Overall shank length = .9615"
Recess dia = .7050"

Recess Depth = .1495"

Go Gauge protrusion = 0.0045"

Turn Tenon Length = 0.9615", Major Dia = 1.0595" for threaded section.



Turn Tenon Length = 0.9615", Major Dia = 1.0595" for threaded section.

Go Gauge protrusion = 0.0045"

Overall shank length = .9615"

ZONE	REV	DESCRIPTION	DATE	APPROVED	COMMENTS:	<div>UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: $\pm 1/32$ ANGULAR: $\pm .2$ TWO PLACE DECIMAL: $\pm .01$ THREE PLACE DECIMAL: $\pm .005$ FOUR PLACE DECIMAL: $\pm .0005$ MATERIAL:</div> <div>DRAWN MKD CHECKED ENG APPR: MFG APPR: Q.A.</div> <div>NAME MKD MFG Q.A.</div> <div>DATE 200 South Front St. Montezuma, IA 50171</div>				TITLE Defiance AntiX Nitride w/ .550 Mag BF SA This is the action that has 3		SCALE: 1:1 SHEET 1 OF 1	
<div>PROPRIETARY AND CONFIDENTIAL</div> <div>THIS ENTIRE DOCUMENT AND ALL THE INFORMATION THEREON IS THE PROPRIETARY AND THE EXCLUSIVE PROPERTY OF BROWNELL'S INC., MONTZUMA, IA, AND SHALL NOT BE REPRODUCED, DISCLOSED, OR COPIED IN WHOLE OR IN PART, EITHER ORALLY OR IN WRITING, OR MADE AVAILABLE TO ANY OTHER PERSON, FIRM, OR CORPORATION OR OTHERWISE USED WITHOUT THE PRIOR WRITTEN PERMISSION OF BROWNELL'S INC., MONTZUMA, IA 50171.</div>						NEXT ASSY USED ON		SURFACE FINISH SURFACE TREATMENT DO NOT SCALE DRAWING		PROTECTION HEAT TREATMENT		SIZ B	