

## Sherman Wildcat Cartridges Load Data

The following loads are a compilation of clients.

There is no SAAMI standard for these cartridges.

All loads should be worked up to with caution.

Any damage or injury resulting from overloads are the sole responsibility of the consumer.

Cartridge	Barrel Length (inches)	Twist (inches)	Bullet/Weight	Powder	Grains	Velocity (FPS)	Length	Brass & Prep	Primer	Notes
6 SST										
	27"	7.5	87 Hornady V-Max	RL 19	56	3530	2.168" BTO	ADG		*vaporizes bullet over this charge
	27"	7.5	110 Sierra Matchking	H1000	52.5	3169	2.223" BTO	ADG		1-2 moa
	27"	7.5	110 Sierra Matchking	H1000	59.5	3451		ADG		
	27"	7.5	115 Berger Hunting VLD	RL 23	55.1	3422	2.333" BTO	ADG		
25 SST										
	26"	7.5	121 Hammer	N565	62	3375		ADG	Fed 215	
	26"	7.5	121 Hammer	H1000	59.5	3414	2.180" BTO	ADG	Fed 215GM	
	26"	7.5	131 Blackjack	N565	61.3	3254		ADG	Fed 210GM	
	26"	7.5	131 Blackjack	H1000	56.5	3136	2.188" BTO	ADG	Fed 215GM	
	24"	7.5	131 Blackjack	N565	60.6	3230	2.850" COAL	ADG	CCI BR-2	
	22"	7.5	131 Blackjack	H1000	60.3	3180	2.895" COAL	ADG		
	26"	7.5	133 Berger Elite Hunter	H1000	58	3187	2.178" BTO	ADG	CCI BR-2	
	26"	7.5	135 Berger LRHT	RL 23	54.5	3127	2.178" BTO	ADG	CCI BR-2	
6.5 SST										
			130 Hornady ELD-M	H4895	42.2	2900	2.870" COAL	ADG	Fed 210	Low Pressure
			140 Berger Hybrid	N565	60.3	3000		ADG	Fed 215	
			140 Berger Elite Hunter	H1000	61	3201	2.150" BTO	ADG	WLRM	
			147 Hornady ELD-M	RL 26	53.5	2981	2.210" BTO	ADG		
			147 Hornady ELD-M	RL 26	57	3107	2.870" COAL	ADG	Fed 210	
			147 Hornady ELD-M	Retumbo	60	3117	2.870" COAL	ADG	Fed 210	
			156 Berger EOL	N565	59	3020	2.150" BTO	ADG	WLRM	
6.555										
			123 Hammer Hunter	IMR 4831	59		2.99" COAL			
			124 Hammer Hunter	RL 23	58.5	3330		ADG	Fed 210GM	
	7		124 Hammer Hunter	RL 23	57	3265		ADG	Fed 215	
			127 Barnes LRX	RL 23	57	3242	2.220" BTO	ADG	Fed 215GM	
	20	7.5	129 Nosler Long Range Accubond	RL 23	56.5	3126	2.250" BTO	ADG		
	26	7.5	129 Nosler Long Range Accubond	RL 23	57	3158	2.230" BTO	ADG	CCI BR-2	
	26	7.5	129 Absolute Hammer	H4350	57	3307			Fed 215GM	Ran to 60 grains at max pressure at 3463fps
	20	7.5	129 Absolute Hammer	H4350	58.5	3222		ADG		Ran to 60.0 grains at 3343 fps max
	20	7.5	130 Sierra TMK	RL 23	55.5	3065	2.282" BTO	ADG		Max pressure 57.5 at 3111 fps
	20	7.5	130 Sierra TMK	N565	58	3006	2.282" BTO	ADG		Near max 61.5 at 3086 fps
	26	7.5	130 Sierra TMK	RL 23	58	3245	2.282" BTO	ADG	CCI BR-2	
	26	7.5	131 Hammer Hunter	RL 26	58.5	3249	2.293" BTO	ADG	Fed 215GM	
	20	7.5	131 Hammer Hunter	RL 26	56	3060	2.293" BTO	ADG	Fed 215GM	58.2 grains 3151 fps
			140 Berger Hunting VLD	RL 23	57	3166	2.230" BTO	ADG	Fed 215GM	
			140 Berger Hybrid	RL 26	60.3	3207		ADG	Fed 210	
			140 Berger Elite Hunter	RL 26	59.7	3226	2.994" BTO	ADG	Fed 210	
	26	7.5	140 Berger Hybrid	RL 23	59	3202	2.282" BTO	ADG		Max
	20	7.5	140 Berger Hybrid	RL 23	57.5	3035	2.262" BTO	ADG	Fed 215GM	50.0 near max 3088 fps
	20	7.5	140 Berger Hybrid	H1000	56.6	2940	2.262" BTO	ADG	Fed 215GM	59.0 near max at 3031 fps
			143 Hornady ELD-X	H1000	62	3180	2.970" COAL	ADG	Fed 210	
	26	7.5	144 Berger LRHT	RL 23	56.5	3114	2.262" BTO	ADG	CCI BR-2	57.5 grains max at 3180 fps
			144 Berger LRHT	N565	58.5	3080	2.262" BTO	ADG	CCI BR-2	60 grains max at 3145 fps
			147 Hornady ELD-M	RL 26	59		2.99" COAL			
			150 Matrix	H1000	62	3120	2.875" COAL	ADG	Fed 210	
			150 Sierra Matchking	H1000	59.5	3114		ADG	CCI BR-2	
	20	7.5	150 Sierra Matchking	N565	59.5	2954	2.267 BTO	ADG	Fed 215GM	
	20	7.5	156 Berger Elite Hunter	N565	61.4	3001	2.268" BTO	ADG	Fed 215GM	Max Load
	20	7.5	156 Berger Elite Hunter	N570	60	2916	2.268" BTO	ADG	Fed 215 GM	Moderate load but full case capacity
	20	7.5	156 Berger Elite Hunter	H1000	58	2921	2.268" BTO	ADG	Fed 215GM	
	26	7.5	156 Berger Elite Hunter	N565	60.5	3068	2.268" BTO	ADG	CCI BR-2	
	26	7.5	156 Berger Elite Hunter	H1000	58	3025	2.268" BTO	ADG	CCI BR-2	
	26	7.5	156 Berger Elite Hunter	N570	60	3042	2.268" BTO	ADG	CCI BR-2	
	26	7.5	156 Berger Elite Hunter	RL 23	57	3084	2.268" BTO	ADG	CCI BR-2	
			160 Matrix	RL 33	63.5	3080	2.880" COAL	ADG	Fed 210	
6.5 Sherman										
			123 Sierra Matchking	H4831	60	3340	3.340" COAL		Fed 210	
			123 Sierra Matchking	Hybrid 100V	55	3230	3.340" COAL		CCI BR-2	
			124 Hammer Hunter	RL 26	63	3360	3.4" COAL		CCI BR-2	
			130 Nosler Accubond	IMR 7828	59	3230	3.374" COAL		CCI BR-2	
			130 Nosler Accubond	H 4831	59.5	3244	3.374" COAL		Fed 210	
			140 Berger VLD	RL 26	61.5	3240	3.552" COAL	Norma	Fed 210	
			140 Berger VLD	RL 26	61.4	3180		Norma	CCI BR-2	
			140 Berger VLD	H1000	62	3123				
			140 Berger VLD	Retumbo	63.9	3145		Norma	Fed 210	
			140 Berger VLD	N570	65.5	32350			Fed 210	
			140 Berger Elite Hunter	RL 26	63	3180				
			140 Nosler Custom Competition	H4831	58	3066	3.392" COAL		WLR	
			140 Nosler Custom Competition	Magpro	60	3012	3.392" COAL		Fed 215	
			140 Nosler Custom Competition	IMR 7828	57.5		3.392" COAL		Fed 210	
			140 Nosler Custom Competition	H1000	62	3133	3.392" COAL		CCI BR-2	
			142 Matrix	H4831	56.3	2970	3.421" COAL		CCI BR-2	
	22		142 Nosler Long Range Accubond	H1000	60	2949	3.450" COAL	Norma	CCI BR-2	
			143 Hornady ELD-X	RL 23	57	3297				
			143 Hornady ELD-X	RL 25	65	3148	3.450" COAL		Fed 210	
			143 Hornady ELD-X	RL 26	63	3203	3.450" COAL		Fed 210	
			143 Hornady ELD-X	IMR 7977	62.5	3138	3.450" COAL		Fed 210	
			150 Matrix	RL 26	60	3127	3.517" COAL	Norma	Fed 210	
			150 Matrix	N570	64.3	3086		Norma	Fed 210	
			150 Matrix	RL 33	70	3117	3.4" COAL		Fed 210	
			150 Matrix	Retumbo	65	3115	3.4" COAL		Fed 210	
			150 Sierra Matchking	RL 26	60	3005	3.4" COAL		Fed 210	
			155 Cauterucio	H1000	61	3009	3.470" COAL		Fed 210	
			155 Cauterucio	Retumbo	61.5	3030	3.470" COAL		Fed 210	
			155 Cauterucio	H 4831	59	2985	3.470" COAL		Fed 210	
			160 Matrix	RL 33	65.5	3045	3.480" COAL	RWS	Fed 210	
			160 Matrix	RL 33	68	3120	3.420" COAL		Fed 210	
			160 Matrix	Retumbo	61.5	2913	3.420" COAL		Fed 210	

			160 Matrix	RL 26	63	3073	3.420" COAL		Fed 210	
<b>6.5 Max</b>										
	22"	7.5	85 Hammer Hunter	IMR 4350	68.5	4002	2.714" COAL	ADG	Fed 210	
	26"	7.5	123 Absolute Hammer	RL 26	64	3143	2.930" COAL	ADG	Fed 210	
			123 Absolute Hammer	RL 26	69.5	3556	2.976" COAL	ADG	Fed 210	
			129 Absolute Hammer	RL 26	68.2	3451	3.020" COAL	ADG	Fed 210	
<b>270 SS</b>										
	21.5"	8.5	130 Nosler Ballistic Tip	IMR 7828	61	3075	2.287" BTO	ADG	CCI 250	Fireforming load, Bullet jammed
	21.5"	8.5	150 Nosler Long Range Accubond	RL 26	58	3080	2.855" COAL	ADG		
	19.5"	8	165 Matrix	N570	63.6	2853	2.204" BTO	ADG	CCI 250	
	19.5"	8	165 Matrix	RL 26	60	2844	2.204" BTO	ADG	CCI 251	
	19.5"	8	165 Matrix	H1000	63	2827	2.204" BTO	ADG	CCI 252	
	19.5"	8	165 Matrix	N565	62	2812	2.204" BTO	ADG	CCI 253	
	19.5"	8	165 Matrix	RL 23	58	2833	2.204" BTO	ADG	CCI 254	Max Charge
	19.5"	8	165 Matrix	Retumbo	64	2868	2.204" BTO	ADG	CCI 255	Max Charge
	24"	8	165 Matrix	RL 23	59.2	2999	2.266" BTO	ADG	CCI 200	
	24"	8	165 Matrix	RL 26	62	2979	2.266" BTO	Norma	Fed 210	
	19.5"	8	175 Sierra Gamechanger	RL 26	57	2750	2.231" BTO	ADG	CCI 250	
<b>270 Sherman</b>										
			126 Cayuga	RL 26	66.5	3425	3.405" COAL	Norma	Fed 210GM	
	19"		140 Badlands SBII	RL 26	63.5	3103	3.5" COAL	Norma	CCI 200	
	27"	8	165 Matrix	RL 26	62	3017	2.905" BTO	Norma	Fed 210	HBN coated, approach with caution, hot load
			170 Berger EOL	RL 33	70.3	3033	2.880" BTO	Norma	Fed 210	
			170 Berger EOL	H1000	63.7	2940		Norma	Fed 215	
	27"	8	170 Berger EOL	Retumbo	65.5	3040	2.870" BTO	RWS		
	27"	8	170 Berger EOL	N570	65.5	2984	2.892" BTO	Norma	Fed 210	
	27"	8	170 Berger EOL	RL 23	60	3019	2.880" BTO	Norma	Fed 210	
	24.5"		170 Berger EOL	RL 26	62.7	2972		Norma	CCI BR-2	
<b>280 Sherman</b>										
	26"	9	180 Berger Hybrid	RL 26	62.5	3020	3.580"	RWS		
<b>7 SS</b>										
	26"		155 Hammer Hunter	H4350	57	3058	2.960"	ADG	Fed 210GM	
	24"	8.4	165 Sierra Tipped Gameking	N565	63	2918	2.270" BTO	ADG	CCI BR-2	64 grains at 3003 fps, max case fill, no pressure
	24"		169 Hammer Hunter	H4831SC	61	2975	2.920" COAL	ADG	CCI 250	
	26"		175 Berger Elite Hunter	Retumbo	63	3000	2.913" COAL	ADG		
	26"		175 Berger Elite Hunter	RL 26	62.5	3030	2.227" BTO	ADG	Fed 210GM	
	21"		175 Hornady ELD-X	RL 26	60	2895				
			180 Hornady ELD-M	H1000	60.1	2843	2.945" COAL	ADG	Fed 210GM	
			180 Hornady ELD-M	RL 26	62.2	3065				
			180 Berger Hybrid	RL 26	61	3010	2.920" COAL	ADG		
			180 Berger Hybrid	N565	64	3005		ADG	CCI 250	
	24"	8.4	184 Berger Hybrid	RL 23	57.5	2797	2.210" BTO	ADG	CCI BR-2	
	24"	8.4	184 Berger Hybrid	N565	62.5	2838	2.210" BTO	ADG	CCI BR-2	63.0 at 2862 fps max case fill no pressure
			185 Nosler RDF	RL 26	58.8	2950	2.860" COAL	ADG		
			190 Hornady A-Tip	H1000	58.3	2720	2.340" BTO	ADG	Fed 210GM	
			195 Berger EOL	RL 26	58	2865	2.945" COAL	ADG		
<b>7 Max</b>										
			120 Hammer Hunter	H4831 SC	72	3619	2.950" COAL	ADG	Fed 215	
			131 Hammer Hunter	H4831 SC	70.7	3545	2.945" COAL	ADG	Fed 215	
			150 Sierra Matchking	H4831 SC	62.2	2987		ADG	Fed 215	
			175 Berger Elite Hunter	RL23	62	3008	3.043" COAL	ADG		
			175 Berger Elite Hunter	RL 25	64		3.058" COAL	ADG	CCI BR-2	
			175 Hornady ELD-X	RL 23	62	3008	3.060" COAL	ADG		
	20"		175 Hornady ELD-X	N565	67	2890	3.015" COAL	ADG	Fed 215GM	
			195 Berger EOL	N570	69	2950	3.085" COAL	ADG	CCI BR-2	
			195 Berger EOL	RL 26	63	2910	2.400" BTO	ADG	CCI BR-2	
<b>7 Mega</b>										
	26"		175 Berger Elite Hunter	N570	74.5	3180	3.248" COAL	ADG	Fed215	
<b>28 Sherman Magnum</b>										
	26"		175 Nosler Long Range Accubond	H1000	74	3023	2.860" BTO		Fed 215	Fireforming load
	26"		195 Berger EOL	Retumbo	73	2810				Fireforming load
	26"		195 Berger EOL	N570	80	3167	2.910" BTO	ADG	Fed 215GM	
<b>300 SS</b>										
	28"	10	180 Berger Elite Hunter	Hybrid 100V	62.5	3090	2.197" BTO	ADG	Fed 210GM	
	28"	10	180 Berger Elite Hunter	RL 16	61.5	3098	2.197" BTO	ADG	Fed 210GM	
	28"	10	180 Berger Elite Hunter	N560	68.5	3095	2.197" BTO	ADG	Fed 210GM	Drop Tube used, Max Capacity
	28"	10	180 Berger Elite Hunter	RL 26	68	3108	2.197" BTO	ADG	Fed 210GM	Drop Tube used, Max Capacity
	28"	10	195 Hornady ELD-M	RL 16	59	2964	2.860" COAL	Norma	Fed 210GM	
	28"	10	195 Hornady ELD-M	IMR 4451	59	2980	2.860" COAL	Norma	Fed 210GM	
	28"	10	195 Hornady ELD-M	RL 22	65	3042	2.860" COAL	Norma	Fed 210GM	Max pressure, Max capacity, Drop tube used
	28"	10	200 Sierra Matchking	RL 16	61	2980	2.207" BTO	ADG	Fed 210GM	
	28"	10	200 Sierra Matchking	N560	67	2966	2.207" BTO	ADG	Fed 210GM	
	28"	10	200 Sierra Matchking	Hybrid 100V	62.5	3030	2.207" BTO	ADG	Fed 210GM	
	28"	10	200 Sierra Matchking	IMR 4451	60.5	2949	2.207" BTO	ADG	Fed 210GM	
	28"	10	200 Sierra Matchking	RL 26	67	3030	2.207" BTO	ADG	Fed 210GM	
	28"	10	208 Hornady ELD-M	RL 26	64.3	2928	2.255" BTO	ADG	Fed 210GM	
	28"	10	210 Nosler RDF	RL 26	64.5	2953		ADG	Fed 210GM	
	28"	10	225 Hornady ELD-M	RL 26	61.8	2795	2.270" BTO	ADG	Fed 210GM	
<b>300 Max</b>										
	21.5"	9	195 Hornady ELD-M	Hybrid 100V	58	2685		ADG	Fed 210GM	Fire Forming load, .030" into lands
	21.5"	9	208 Hornady ELD-M	RL 26	68	2893	2.318" BTO	ADG	Fed 210GM	Work up to this, Do not start here
	22"	9	208 Hornady ELD-M	Hybrid 100V	62.1	2810	3.005" COAL	ADG	Fed 215	
<b>30 Sherman Magnum</b>										
			200 Hornady ELD-X	H1000	78	2948	2.805" BTO	ADG	Fed 215	
			215 Berger Hybrid Target	RL 23	76	3071	3.715" COAL	Hornady		
			215 Berger Hybrid Target	RL 33	90	3190	3.715" COAL	Hornady		Maximum Load
			215 Berger Hybrid Target	H1000	82	3050	3.715" COAL	Hornady		
	28"	10	225 Hornady ELD-M	N 570	83.3	3050	3.775" COAL	Hornady	WMR	
			230 Berger OTM	N 570	83	3050	3.650" COAL	Hornady	WMR	
			230 Berger Hybrid Target	N 570	83	3045		Hornady		
			245 Berger EOL	N 570	83	3000	3.300" BTO	ADG	Fed 215	
<b>338 SS</b>										
			230 Hornady ELD-X	Varget	61.4	2884	2.165" BT)			

[illegible]